



# NANDO 502 WASH

PURE EMOTION



## OPTICS

- 2-element 15:1 zoom high-resolution optic system
- Beam aperture: 3.5° to 53°
- Fast motorised linear zoom
- 12 truncated edges 70 mm front lenses
- 210 mm front lens cluster

## LIGHT SOURCE

- 12 x 1,000 lumens RGB-L High-Power LED sources
- Total luminaire output: up to 10,000 lumens
- CRI: greater than 86
- Rated life (L70): up to 40,000 hours
- Flicker free sources management, suitable for TV applications and all video recorded events

## MOVEMENT

- Extremely accurate positioning
- Moving-head operated via either 8- or 16-bit resolution
- High-resolution stepper motors operated via microprocessors ensure extreme accuracy and smooth movement.
- PAN and TILT automatic repositioning
- Moving-head range: 540° pan & 270° tilt

## COLOURS

- Sophisticated 4 colours RGB-L mixed, reaching high Colour Rendering Index
- Uniform light beam with no colour shadows, and rich saturated and pastel colour-hues
- 4.29 billion colours (8 bit resolution)
- Virtual colour wheel, including most usuals white colour temperature presets

## EFFECTS

- 2D & 3D graphical effects capabilities
- Effects can be coupled with beam, wash or matrix applications
- Built-in pattern effects with speed and fade controls for scenic applications
- Individual control of each pixels

## DIMMER / STROBE

- Electronic dimmer, allowing perfect light adjustment from 0 to 100% without colour variation
- White or colour strobe effect, with speed adjustment from 1 to 25 flashes per second

## SOFTWARE FEATURES

- Local DMX addressing of luminaire and optional parameters through its built-in LCD control panel
- Remote DMX addressing of luminaire and optional parameters through a standard RDM DMX controller
- Information menu including hour counter, temperature, software version

## HARDWARE FEATURES

- Graphic LCD display for addressing and special functions settings, with flip function
- 5 menu buttons to set functions
- Excess temperature protection
- Integrated wireless CRMX TiMo™ RDM receiver from LumenRadio™
- XLR 5 pin male and female connectors for DMX connection
- etherCON RJ45 IN / OUT connectors for ArtNet™ connection
- powerCON TRUE1 IN / OUT connectors for power connection

## CONTROL

- DMX 512 protocol, through DMX cable
- DMX-RDM compatible
- Stand-alone mode and Master/Slave modes
- ArtNet™ & sACN protocol through Ethernet cable
- Local control panel, with LCD display
- Choice of 3 DMX modes (26 to 86 DMX channels)

## POWER SUPPLY

- Electronic supply with active PFC
- 100 to 240 Volts - 50/60Hz
- Power: 550 W maximum

## COOLING SYSTEM

- Advanced cooling system
- Self adjusting variable speed fans for quiet operation (Auto mode)
- Selectable auto, stage & silence ventilation modes
- Safety protection against temperatures excesses

## HOUSING

- Skeleton made of aluminium and steel plates
- Base in die-cast aluminium
- Heatsinks in aluminium
- Moulded covers in self-extinguishing fire retardant ABS PC (V0 class) Two sides handles for transportation
- Four heavy-duty feet for better stability
- IP65 protection rating
- Exterior finish: black (Carbon)

## INSTALLATION

- Fastening brackets system: two Omega 1/4 turn brackets designed for use with standard clamps
- Mounting points: four 1/4 turn locking fittings allowing installation of Omega brackets on luminaire
- Safety cable attachment point

## OPERATING PARAMETERS

- Operating positions: all (device on floor or fixed to a support)
- Maximum permitted ambient temperature (Ta max): 45°C (113 °F)
- Minimum permitted ambient temperature (Ta min): -20 °C (-4 °F)
- Minimum usage distance: 1m (3.28 ft)

## COMPLIANCE

### EU (EMC & LVD)

- EMC Directive 2014/30/EU
- LVD Directive 2014/35/EU

### US (Safety & EMC)

- UL 1573
- FCC Part 15, Subpart B:2018

## SIZE

- Product: 342 x 467 x 268 mm (l x h x d)
- Flight-case foam: 395 x 480 x 335 mm (l x h x d)

## WEIGHT

- Product: 14.5 kg

## PRODUCT CODES

- 013420: NANDO 502 WASH - IP65 MULTI-SOURCES 6 SERIES

## LEGAL

- NANDO is AYRTON registered Trademark
- NANDO is a patented model

Confidentiality Notice: This document is confidential and contains proprietary information and intellectual property of AYRTON. Neither this document nor any of the information contained herein may be reproduced or disclosed under any circumstances without the express written permission of AYRTON. Please be aware that disclosure, copying, distribution or use of this document and the information contained therein is strictly prohibited.

Product shown are for illustration purposes only. Specifications subject to change without notice.