grandMA3 I/O Node PoE

Art.-No. 4023577-1



The grandMA3 I/O Node PoE is the multi-tool of signal distribution within a grandMA3 system. Wherever the signal is generated or needed – just place a grandMA3 I/O Node PoE there and receive or send external signals.

The grandMA3 I/O Node PoE comes in a 9.5" 1RU housing. It can be fully powered by PoE (Power over Ethernet) to reduce additional cabling. A wide range of accessories allows for alternative fixing methods and customization if required.The 3.9" color display shows the status of all input and output signals. Just add the grandMA3 I/O Node PoE as a Session Member and it is ready to go.

It has never been easier to integrate external signal flows into the MA-Net workflow. Once a grandMA3 I/O Node PoE receives MIDI, Timecode or DC Remote signals, these are available immediately throughout the grandMA3 system, and can be used in any grandMA3 console or onPC station. The same is true for transmitting MIDI or Timecode signals.

Scope of delivery

Art.-No.	Article	Quantity
4025836	MA Quick Manual for grandMA3 I/O Nodes	1

1x powerCON TRUE1 socket (NAC3FX-W-TOP) or similar

Technical Specifications

Parameters	none
Parameters Mode2	none
Operating voltage/ Supply voltage	AC 100 - 240 V; 50/60 Hz PoE (IEEE 802.3af; 48 V DC/max. 12 W)
Power	max. 15 VA
Operating Temperature	0 °C up to 40 °C / 32 °F up to 104 °F
Dimensions	207 x 184 x 43 mm / 9 x 8 x 2 in (width x depth x height)
Net weight	2 kg / 5 lbs
Connectors	1 x powerCON TRUE1 1 x etherCON/RJ45 1 x MIDI In (5pin DIN female) 1 x MIDI Out (5pin DIN female) 1 x Linear Timecode (3pin XLR female) 1 x GPI General Purpose Interface (D-SUB DE9 female) for remote control 1 x USB 2.0 (type A)

Article

Art.-No.	Article
4023577-1	grandMA3 I/O Node PoE

Accessories

Art.-No.	Article
130281	MA 2Port Node / 4Port Node 19" rack mounting kit – blank panel
130283	MA 2Port Node / 4Port Node 19" rack mounting kit – 2x Nodes
130284	MA 2Port / 4Port / 8Port Node rigging plate

More product pictures



