



**BORA NEW MENU**  
**From Software V201**

Address	Address	DMX address:001-XXX :	
Mode	User Mode	Stand Mode Basic Mode Extend Mode User Mode A User Mode B User Mode C	
	Edit User ModeA :	Max channel PAN :	
Options	Status	No DMX Mode Pan Reverse Tilt Reverse Pan Degree Feedback Init PAN Init TILT Pan/Tilt Spd Hibernation Art-Net to DMX	Close/Hold/Auto ON/OFF ON/OFF 630/540 ON/OFF ON/OFF ON/OFF Speed 1~ 4 OFF , 01M~99M ON/OFF
	Service PIN	Service PIN Set Ip Cross Load SW Clr LED Timer	Password=XXX xxx.xxx.xxx.xxx ON/OFF ON/OFF
	Fans Control	Fans Speed	Auto Stage Silence Super Silence
		Constant Fans	ON/OFF
	Disp.Setting	Shutoff Time Flip Display Key Lock	02~60m 05m ON/OFF ON/OFF ON/OFF

		DispFlash	
	Signal Select	DMX WDMX Art-Net sACN	
	Temp. C/F	Celsius Fahrenheit	
	Initial Pos.	PAN =XXX	
	Wireless DMX	Activate WDMX Act&Data Out Rest WDMX	
	Dim Curve	Square Law Linear	
	Refresh Select	1.2K 2.4K 16K 25K	
	Trigger	DMX Value Disp. Set To Slave Auto Program	PAN..... Slave1,Slave2,Slave3 Master / Alone
	ResetDefault	ON/OFF	
Info	Time Info.	Current Time Ttl Life Hrs Last Run Hrs LED Hours Timer PIN Clr Last Run	
	Temp. Info	Head Temp.	
	Fan Info.	xxxxRPM	
	Software Ver	V1.0.....	
	Network	IP,Mask,Mac	
Test	Home	All Pan&Tilt Color Gobo Other	
	Test Channel	PAN .....	
	Manual Ctrl.	PAN =XXX :	
	Calibration	-Password- PAN :	

<b>Preset</b>	Select Prog.	Prog. Part 1 = Program 1 ~ 10 <b>Program 1</b> Prog. Part 2 = Program 1 ~ 10 <b>Program 2</b> Prog. Part 3 = Program 1 ~ 10 <b>Program 3</b>	
	Edit Prog.	Program 1 : Program 10	Program Test Step 01=SCxxx Step 64=SCxxx
	Edit Scenes	Edit Scene 001 ~ Edit Scene 250	Pan,Tilt,..... --Fade Time-- --Secne Time-- Input By External Device
	Scenes Input	XX~XX	