

Light is OSRAM

OSRAM

Our Brand

e:cue

## SYMPL bridge Node

### e:cue Interfaces

Lighting applications are heterogenous by nature. e:cue interfaces serve to integrate many networks, protocols and third party products into e:cue solutions. They also aid in applying special control functions for fixtures, they integrate analog or mechanical signaling into the digital world and offer bridging functions. e:cue interfaces are the links to bring together the many techniques and technologies of lighting control.



### e:cue SYMPL bridge Node

The SYMPL bridge Node is a Art-Net / e:net / sACN to DMX / e:pix interface. Switch between two input sources on the fly. It comes with 8 x DMX / e:pix universes over screw terminal plugs. The SYMPL bridge Node makes it possible to run up to 4096 DMX channels (= 1360 RGB pixels, 170 pxl/universe) via DMX universes and up to 16,384 DMX channels (= 5456 RGB pixels, 682 pxl/universe) via e:pix universes. The SYMPL bridge Node supports up to 32 Art-Net / sACN universes. It is especially designed for projects in tough outdoor environments. Connection to the server runs via Ethernet interface with 100 Mbit/s. The Bridge can be powered by an external power supply or via Power-over-Ethernet. It is easily mounted on standard 35 mm DIN rails, or with a key hole in the housing base on walls or on any stable vertical surface. The SYMPL bridge Node is a simple, reliable and easy to use interface solution for e:cue's lighting control solution SYMPHOLIGHT.

### Highlights

- Art-Net / e:net / sACN to DMX / e:pix interface with 8 x DMX512 / e:pix outputs
- Supports up to 32 Art-Net / sACN universes
- sACN in unicast or multicast mode
- Flexible mounting on 35 mm DIN rails or vertical surfaces
- Simple and easy integration in e:cue SYMPHOLIGHT
- Extended operating temperature -40 ... 70°C
- Backup-mode on data loss
- Integrated protection against surge; Highly isolated outputs
- Reverse polarity protection
- Power-over-Ethernet
- Test mode via button
- Web interface for status and configuration

### Delivery scope

- e:cue SYMPL bridge Node
- Safety instructions, Welcome note

### Identcode

AM356970031

### Optional accessories

- Power supply 15W 24V DIN rail

AM1884100HA

### Product

SYMPL bridge Node

### Product number

AM356970031

### Dimensions

(W x H x D)

143 x 92 x 62 mm/

5.63 x 3.6 x 2.4 in (excl. fastening clip)

### Weight

250 g / 0.55 lb

### Power supply input

24 ... 48 V DC (terminal plug), cable cross section: 0.205 – 3.31 mm<sup>2</sup>, reverse polarity protection or PoE IEEE 802.3af on RJ45

### Power consumption

max. 8 W (incl. DMX termination)

### Operating temperature

-40 ... 70 °C \* / -4 ... 158 °F \*

### Storage temperature

-40 ... 70 °C / -4 ... 158 °F

### Operating / storage humidity

0 ... 80% RH, non-condensing

### Protection class

IP20

### Electrical safety class

SELV

### Housing

Self extinguishing blend PC/ABS UL E140692

### Mounting

on 35 mm DIN rail (EN 60715), or with key hole on any stable vertical surface

### Interface specifications

#### Interfaces

8 x DMX512 / 8 x e:pix isolated in pairs, surge protection, 3-pin terminal plug cable cross section: 0.081 – 1.31 mm<sup>2</sup>

#### Interface specifications

 $V_{DMXmax} / V_{DMXmin} = 4.6 V / 0.8 V$   
Short circuit protected:  $I_{SCmax} = 100 mA$ 

#### Ethernet-Port

1 x e:net 10/100 Mbit/s RJ45, surge protection

#### Sensors, internal

Temperature -40 ... 120 °C (±0.2 °C) / -40 ... 248 °F (±0.36 °F)  
Humidity 0 ... 100% (±2%)

continued on next page

Light is OSRAM

# OSRAM

Our Brand

## ecue

## SYMPL bridge Node

User interfaces      LEDs for Test / Error, Ethernet activity,  
device status, DMX status  
Identify button, Test button

\*) 70 °C / 158 °F for max. 1 hour/day;  
continuous operation at max. 60 °C / 140 °F.



Intertek  
4000805

Conforms to ANSI/UL Std. 62368-1  
Certified to CSA Std. C22.2 NO. 62368-1



### Dimensions

All measures in mm

