gx 3 specs





Take live events to the next frontier

The gx 3 is the new go-to media server for touring artists who want to run the most intricate set designs.

Warranties & Support

- 2 year return to base hardware warranty

Physical specifications


Bundled accessories	Packed Dimensions:	₩ 610mm 24"	H 395mm 15.5"	D 765mm 30"
Keyboard Mouse Power Cable (Plug-True1) Hardware Guide	Unit Dimensions:	W 445mm 17.52"	H 178mm 7"	D 593mm 23.35"
	Unit + Rack Handles	W 483mm 19"		D 621mm 24.45"
Rack slides	Rack Depth:			D 585mm 23.03"
Upgrades (AS - At Sale, F - Field)	Unit Weight:		14.4 kg 31.75 lbs	
– Storage Upgrade 7.68TB ^{AS, F} – Storage Upgrade 15.35TB ^{AS, F}	Packed Unit Weight:		20.46 kg 45.1 lbs	


Software

- Notch Playback Licence (2 years)

gx 3 specs

disguise





Hardware specifications

Voltage: 100-240V, 50-60Hz Power Connection: Neutrik powerCON True1 Power Consumption Peak: 700 W Heat Dissipation Peak: 2,388 BTU/hr Max decibel rating: 56dB

Environmental Tolerances: Temperature: 5-35°C (40°-95°F) Humidity: 5%-95% (noncondensing) Altitude: 0-2700m (0-8850 ft)

Operating System: Windows 10 Enterprise SAC OS: 2× 256GB SSD Storage: 3.84TB SSD (default)

System connectivity I/O

Video Output:

1× DisplayPort 1.4 (GUI) 3× VFC Output Slots Ships standard with HDMI 2.0 VFC cards

Different Video Format Conversion Cards also available, refer to VFC specifications

Video Input:

3× 12G inputs or 12× 3G inputs (HD-BNC connectors)

Audio:

Balanced XLR (circular 3-pin connector) - 2× in, 2× out Analogue (1/4 headphone jack) - 1× in

Optical Audio: ADAT/SPDIF (Toslink connector) - 1× in, 1× out MIDI:

MIDI (circular 5-pin DIN connector) - 1× in, 1× out

Video Sync: 1× BNC Genlock

Data/Peripherals:

Controller:

5× USB 3.0

General Network:

1× 1Gb/sec Ethernet

2×10Gb/sec Ethernet

High Speed Network:

2× 100Gb/sec Ethernet

System Management

1× Management Port (Ethernet)